

MuteMat OSF 750-10

Product Data

riba
product
selector

Description: Mutemat OSF 750-10 is our high performing floor acoustic insulation. MuteMat consists of a highly recycled rubber-mix which acts as a dense, resilient layer suitable for concrete structures to attenuate impact noise. MuteMat can be used under a range of floor finishes. It offers greater stability and durability due to the lack of deformation.

Dimensions: 10mm x 1.3m x 5m
Roll Area: 6.5m²
Roll Weight: 50 kg
Density: 750 kg/m³
Mass: 7.5 kg/m²
Compression Loads: 10 kN/m² = < 7% loss of thickness.
(Over 10 Years) 15 kN/m² = < 10.6% loss of thickness.
20 kN/m² = < 14.3% loss of thickness
Recycled Content: 1.86 Recycled tyres per m² - 12.09 Recycled tyres per roll
92% Recycled - 100% Recyclable

Features and Benefits: Significantly reduces impact sounds.
Can be installed under finished flooring.
Guaranteed constant thickness and density.
Does not deform, maintains efficiency long term.
Pre-fabricated recycled tire granule mat.
Low compression under heavy loads.
May be used in retrofit.

Performance: Reduction from MuteMat OSF 750-10: ΔL_w 23dB

*Performance will vary with different floor make-up.
Please see performance data for examples.*

