MAINTENANCE

New Era Gymflex is a high performance sports surface that will last a long time when looked after In order to maintain the high performance floor surface and to prolong the life of the floor we recommend the following:

Daily Cleaning	Sweep and remove debris using an anti-static mop or similar.
Cleaning every 1-2 weeks	Use NE Clean solution to clean floor using mop or mechanical
Buff & Seal	Approx every 18 months we recommend a deep clean, buff and application of NE Sports lacquer to ensure surface remain in good condition.
Sand and seal	Normal use would mean a sand and reseal is needed approximately every 7 years. This would be a full sand back to bare wood and the use of the NE Prime and 3 coats of NE lacquer.

NEW ERA NE CLEAN



New Era NE Clean is a multi purpose everyday cleaner designed to dissolve surface dirt that dries quickly and not leaving a film on the floor. With a mop or mechanical floor cleaner, ensuring a minimal amount of water is in contact with the floor. When using mops it is essential to ensure it is always well wrung out and kept clean.

Dilute: 50-100ml/10 litres of water

NEW ERA NE PRIME



New Era NE Prime is a water based quick drying primer for all untreated timber Floors, NE Prime limits side-bonding between individual planks and gives a perfect base coat for the New Era NE lacquer.

Application: Use a suitable lacquer roller or applicator for perfect results

Coverage: 5 Itr can - Approx. 40m2 **Re-coat time:** Approx. 30 minutes

NEW ERA NE LACQUER



New Era NE Lacquer is a two-component water based sports lacquer especially for high traffic sports floors that can be applied over existing finished floors or on new sanded floors.

(NE Prime must be used first on sanded floors)

Application: Use a suitable lacquer roller or applicator for perfect results

Coverage: 5 Itr can - Approx. 40m2 **Re-coat time:** Approx. 2.5-3 hours

Finish: Silk Matt