

MS500 ADHESIVE

PRODUCT DESCRIPTION

MS500 Wood Floor Adhesive from New Era is a high strength, single-part silane polymer adhesive. The advantages of MS500 is that it can be used for bonding most types of wood flooring - including wood blocks, engineered, laminated & solid wood plank flooring and the New Era Range of Acoustic Underlays.

MS500 is also compatible with underfloor heating systems. It cannot be used over bitumen based subfoors.

This adhesive is compatible over most substrates including sand and cement screeds, concrete, Anhydrite (Calcium Sulphate) screeds, stone and timber.

For compatibility confrmation with the underfloor heating systems contained within the substrate contact the Technical Team.



TECHNICAL INFORMATION

Coverage Rate:	Approx 1-1.3kg per m2 with 4mm or B6 triangular notch trowel.
Cleaning:	Can be removed by the use of multi purpose surface wipes whilst adhesive is still wet. Cured adhesive can be removed mechanically.
ShelfLife:	12 months when stored as recommended in original unopened packaging.
Packaging:	Available in 17kg/10 ltr plastic buckets.
Storage:	Store in dry conditions between +5°C and +25°C.
Colour:	Brown
Working Time:	20 mins approx. depending on atmospheric conditions.
Application Temperature Range:	+15°C to +35°C. R.H. Maximum 70%