


INSTALLATION INSTRUCTIONS




GYMFLEX ACTIVE SOLID INSTALLATION INSTRUCTIONS



1. Lay 1000 gauge polythene with 150mm overlapped and taped joints. Lap up wall passed finished floor height.



2. Flexjoist Centres to be set out at 366mm and cradles along the flexjoist set out at 450mm if using a 36mm flexjoist or 600mm if using a 48mm flexjoist



3. Sports cradles to be adjusted to datum using Laser level and New Era packers fitted to cradles.



WATCH INSTALLATION VIDEO

Note: On every installation the subfloor must be checked to ensure compliance with BS8201 and no system should be laid on concrete substrates unless RH is tested and recorded to be below 75% RH (65% if it has underfloor heating)

Building should be weathertight and Relative Humidity (RH) be stable and between 35-65%

GYMFLEX ACTIVE SOLID INSTALLATION INSTRUCTIONS



4. Fit Flexjoist to cradles, ensuring each row is staggered to make sure floor is fully tied in. Leave minimum of 40mm expansion off wall on ends of every Flexjoist.

5. Lay floor with header joints staggered at 366mm centres fully supported on a flexjoist. 0.8mm spacers to be fitted every 2 rows in main field of floor whilst laying. Floor to be nailed on every row and every flexjoist using L or T flooring nails. 1.5mm expansion required in the field of floor for every 1 metre of width - eg. (10m = 15mm)



SCAN ME



WATCH INSTALLATION VIDEO

Note: On every installation the subfloor must be checked to ensure compliance with BS8201 and no system should be laid on concrete substrates unless RH is tested and recorded to be below 75% RH (65% if it has underfloor heating)


Building should be weathertight and Relative Humidity (RH) be stable and between 35-65%

INSTALLATION INSTRUCTIONS


GYMFLEX ACTIVE LAYERED INSTALLATION INSTRUCTIONS




1. Lay 1000 gauge polythene with 150mm overlapped and taped joints. Lap up wall passed finished floor height.



2. Flexjoist Centres to be set out at 366mm and cradles along the flexjoist at 450mm for 36mm flexjoist and 600mm for 48mm flexjoist



3. Sports cradles to be adjusted to datum using Laser level and New Era packers fitted to cradles.



WATCH INSTALLATION VIDEO

Note: On every installation the subfloor must be checked to ensure compliance with BS8201 and no system should be laid on concrete substrates unless RH is tested and recorded to be below 75% RH (65% if it has underfloor heating)


Building should be weathertight and Relative Humidity (RH) be stable and between 35-65%

GYMFLEX ACTIVE LAYERED INSTALLATION INSTRUCTIONS



4. Fit Flexjoist to cradles, ensuring each row is staggered to make sure floor is fully tied in. Leave minimum of 40mm expansion off wall on ends of every Flexjoist.

5. Lay floor with header joints staggered at 366mm centres with all ends glued using P300 adhesive and fully supported on a flexjoist.
Floor to be nailed on every row and every flexjoist using L or T flooring nails.
No expansion required in the field of floor and 15mm expansion to all abutments.



SCAN ME




WATCH INSTALLATION VIDEO

Note: On every installation the subfloor must be checked to ensure compliance with BS8201 and no system should be laid on concrete substrates unless RH is tested and recorded to be below 75% RH (65% if it has underfloor heating)

Building should be weathertight and Relative Humidity (RH) be stable and between 35-65%

GYMFLEX ACTIVE



GYMFLEX ACTIVE
FLEXJOIST & CRADLE
LAYOUT

Solid Flooring

Flexjoist Size		A	B	C	D	E
36mm	Layout >	Flexjoists 366mm	Cradles 450mm	Flexjoist Stagger >	Flexjoists 900mm	Flexjoists 1800mm
48mm		Flexjoists 366mm	Cradles 600mm		Flexjoists 1200mm	Flexjoists 1800mm

Layered Flooring

Layout		Flexjoists 366mm	Cradles 450mm	Flexjoist Stagger >	Flexjoists 900mm	Flexjoists 1800mm	Floor 366mm
36mm	>						
48mm		Flexjoists 366mm	Cradles 600mm		Flexjoists 1200mm	Flexjoists 1800mm	Floor 366mm

The Gymflex Active pre-finished floor is available in a range of different colour options to help with the expression and creativity, which will enhance any Multi-use space with a great contemporary decor, whilst delivering the performance required

GYMFLEX ACTIVE SOLID FLOOR FINISH OPTIONS



RUMBA



SAMBA



CUBAN



NATURAL



FUMED



MIST



FUMED MIST

GYMFLEX ACTIVE LAYERED FLOOR FINISH OPTIONS

